

Impulse – Shut Off and Non Shut Off



NON SHUT OFF

PICTURE REF	TOOL TYPE	PART NUMBER	FREE SPEED	OUTPUT	TORQUE RANGE	LENGTH	WEIGHT	AIR FLOW	AIR HOSE BORE	AIR INLET ⁽¹⁾	SOUND LEVEL ⁽²⁾	VIBRATION
			r/min		ft lb	ins	lb	scfm	ins	NPT	dB(A)	ms ⁻²
A	PT008-L10500-I4Q	1461384	10500	1/4" hex	3.0-5.9	9.4	2.09	10.6	5/16"	1/4"	72	<2.5
A	PT013-L10500-I4Q	1461394	10500	1/4" hex	5.9-9.5	10.4	2.20	10.6	5/16"	1/4"	72	<2.5
B	PT030-L9000-I10S	1461404	9000	3/8" sq	11.0-22.1	9.7	2.64	10.6	5/16"	1/4"	73	<2.5
C	PT009-T7800-I4Q	1461414	7800	1/4" hex	3.7-6.6	7.2	2.09	12.7	5/16"	1/4"	76	<2.5
C	PT016-T7800-I4Q	1461784	7800	1/4" hex	6.6-11.8	8.2	2.31	12.7	5/16"	1/4"	76	<2.5
D	PT035-T9000-I10S	1461424	9000	3/8" sq	14.8-25.8	6.9	2.16	12.7	5/16"	1/4"	77	<2.5
E	PT070-T7500-I13S	1461434	7500	1/2" sq	31.0-51.6	7.0	4.40	14.8	5/16"	1/4"	79	<2.5
F	PT115-T6000-I13S	1461444	6000	1/2" sq	55.3-84.8	7.3	5.94	19.1	3/8"	3/8"	78	2.5
F	PT200-T5500-I13S	1461454	5500	1/2" sq	88.5-147.5	7.1	7.26	23.3	3/8"	3/8"	81	2.7
F	PT250-T4000-I19S	1461464	4000	3/4" sq	118.0-184.4	9.1	9.46	25.4	3/8"	3/8"	80	4.5

SHUT OFF

PICTURE REF	TOOL TYPE	PART NUMBER	FREE SPEED	OUTPUT	TORQUE RANGE	LENGTH	WEIGHT	AIR FLOW	AIR HOSE BORE	AIR INLET ⁽¹⁾	SOUND LEVEL ⁽²⁾	VIBRATION
			r/min		ft lb	ins	lb	scfm	ins	NPT	dB(A)	ms ⁻²
G	PT010-L5000-S4Q	1462254	5000	1/4" hex	3.7-7.3	8.3	1.98	12.7	5/16"	1/4"	74	<2.5
G	PT014-L6000-S4Q	1462264	6000	1/4" hex	5.9-10.3	8.3	1.98	12.7	5/16"	1/4"	74	<2.5
H	PT010-T5500-S4Q	1462274	5500	1/4" hex	3.7-7.3	6.5	2.09	12.7	5/16"	1/4"	74	<2.5
H	PT014-T6000-S4Q	1462284	6000	1/4" hex	5.9-10.3	6.5	2.20	12.7	5/16"	1/4"	74	<2.5
I	PT040-T6000-S10S	1462294	6000	3/8" sq	16.2-29.5	7.0	3.08	17.0	5/16"	1/4"	77	<2.5
J	PT070-T4000-S13S	1462304	4000	1/2" sq	23.6-51.6	7.6	3.96	21.2	3/8"	1/4"	81	<2.5
K	PT125-T3500-S13S	1462314	3500	1/2" sq	45.7-92.2	7.9	5.28	25.4	3/8"	1/4"	81	3.3

⁽¹⁾ BSP optional

⁽²⁾ Sound level measured to test code PN8NCT1.2

Lou Zampini & Associates
 2 Douglas Pike, Rt. 7
 Smithfield, RI 02917
 1 800 353 4676
 FAX 1 401 679 0165

