

Desoutter



Desoutter Limited, HP2 7DR, UK

S4X2A

(GB) Servicing Instructions
Parts List
Operating Instructions

(D) Wartungsanleitung
Teilleiste
Bedienungsanleitung

(F) Manuel d'entretien
Liste de pièces
Manuel d'utilisation

(E) Instrucciones de Servicio
Listas de Repuestos
Instrucciones de Operación

(P) Instruções de Manutenção
Listas de Peças
Instruções de Funcionamento

(I) Istruzioni per la Manutenzione
Elenco delle Parti
Istruzioni Operative

(GR) Οδηγίες Συντήρησης
Κατάλογοι Ανταλλακτικών
Οδηγίες Λειτουργίας

(NL) Onderhoudsinstructies
Onderdelenlijst
Bedieningsinstructies


(DK) Servicevejledning
Liste over dele
Betjeningsvejledning

(N) Serviceinstruksjoner
Delelister
Driftsinstruksjoner


(S) Serviceinstruktioner
Reservdelslista
Bruksanvisning

(FIN) Huolto-ohjeet
Osaluettelo
Käyttöohjeet

ISO 1173	B.3	F6.3
S4X2A-1000	1225774-E	1223494-E
S4X2A- 800	1225854-E	1223574-E
S4X2A- 500	1225934-E	1223654-E



Item Ps. Nr. No. Article	Part No. Teil Nr. Référence	Qty Menge Qté	Item Ps. Nr. No. Article	Part No. Teil Nr. Référence	Qty Menge Qté	Item Ps. Nr. No. Article	Part No. Teil Nr. Référence	Qty Menge Qté
1	280873	2	35	281283	1	67	256763	1
2	281683	2		(800RPM)		69	380903	1
3	281363	2		281293	1	70	280893	1
4	280103	1		(500RPM)		71	280413	1
5	280533	1	36	280673	3		(Blue)	
6	457803	1		(1000RPM)		72	280433	1
7	293373	2		280763	3		(Red)	
8	262303	1		(800RPM)		73	292583	1
9	260673	1		280683	3			
10	280553	1		(500RPM)				
11	281653	1	37	224173	1			
12	280933	1	38	280613	1			
13	292693	1	39	280513	1			
14	280093	1	40	280053	1			
15	280883	1		(B3)				
16	280833	1		296103	1			
17	280223	1		(F6.3)				
18	259783	3	41	280473	1			
19	259913	1	42	3893	3			
*20	203713	1	43	280463	1			
*21	280843	1	44	280373	2			
22	280813	1	45	280423(G)	1			
	(1000RPM)		*46	157303	1			
	280823	1	47	280403	1			
	(800RPM)		48	280383	1			
	(500RPM)	1	*49	280353	1			
23	280863	1	*50	280343	1			
24	280923	3	51	280323	1			
25	281673	3	52	280313	7			
26	280773	1	53	280393	1			
27	280783	1	54	280363	1			
28	280733	1	55	280333	1			
29	280523	1	56	281633	1			
30	280593	1		(B.3)				
31	280493	1	*57	280253	1			
32	280713	2	58	320853	1			
33	281213	1	*59	320713	1			
	(1000RPM)		60	280063	1			
	281223	1	61	411703	1			
	(800RPM)		62	286073	1			
	281233	1		(F6.3)				
	(500RPM)			280143				
34	280763	3		(B.3)				
	(1000RPM)		63	296113	1			
	280683	3		(F6.3)				
	(800RPM)		*64	296043	1			
	(500RPM)		65	72408	1			
35	281273	1	66	296033	1			
	(1000RPM)			(F6.3)				



**Manual or Automatic mode
Hand-oder Automatikbetrieb
Mode Manuel ou Automatique**

for Manual operation
für Handbetrieb
pour fonctionnement Manuel

for Automatic operation
für Automatikbetrieb
pour fonctionnement Automatique

**Primary direction of rotation
Hauptdrehrichtung
Direction primaire de rotation**

Bias switch to direction required.

Richten Sie den Schalter zum bevorzugten Betrieb aus

Polariser le commutateur le mode requis.

- (GB)** * Indicates normal replacement items. It is recommended that adequate stocks are held for servicing requirements. Always quote tool model number, serial number and spare part number when ordering spares.
- (D)** * Bedeutet normale Verschleißteile. Es empfiehlt sich eine angemessene Menge für Wartungszwecke auf Lager zu halten. Bei der Bestellung von Ersatzteilen, bitte immer angeben: Typennummer der Bohrmaschine, Werknummer und Ersatzteilnummer.
- (F)** * Le symbole astérisque (*) indique des articles de rechange normaux. Il est recommandé d'en conserver des stocks suffisants pour assurer toutes les opérations d'entretien courant. Lors de la commande de pièces de rechange, toujours citer le numéro de modèle de l'outillage, son numéro de série et le numéro de référence de chaque pièce de rechange.
- (E)** * Indica elementos de reposición regular. Se recomienda tener una cantidad adecuada de los mismos en reserva a efectos de mantenimiento. Al encargar piezas de recambio, siempre debe indicarse el número de modelo de la herramienta, su número de serie y el número de la pieza de recambio.
- (P)** * Indica itens que são substituídos regularmente. É recomendado que estoques adequados sejam mantidos para requisitos de manutenção. Cite sempre o número do modelo da ferramenta, número de série, e número da peça acessória quando pedindo acessórios.
- (I)** * L'asterisco denota ricambi normali. Si consiglia di mantenere scorte adeguate alle esigenze della manutenzione. Nell'ordinazione di ricambi citare il numero di modello dell'utensile, il numero di matricola e quello di catalogo del pezzo.
- (GR)** * Σημαίνει συνηθισμένα είδη (τεμάχια) για αντικατάσταση. Σας συνιστούμε να τηρείτε αρκετό απόθεμα από τα είδη που χρειάζονται αντικατάσταση. Όταν παραγγέλνετε ανταλλακτικά πάντα να γράφετε τον αριθμό μοντέλου του εργαλείου, τον αριθμό σειράς και τον αριθμό ανταλλακτικού.
- (NL)** * Betekent normale reserveartikelen. Het verdient aanbeveling om voldoende voor onderhoudsbehoeften voorradig te hebben. Bij bestelling van reserveonderdelen geef altijd modelnummer, volgnummer en reserveonderdeelnnummer van het werktuig op.
- (DK)** * Indikerer normale udskiftningsemner. Det anbefales at have rigelige forsyninger af dele til brug i forbindelse med eftersyn. Opgiv altid det korrekte værktøjsmodelnummer, serienummer og reservedelsnummer ved bestilling af reservedele.
- (N)** * Angir normale reservedeler. Det anbefales at tilstrekkelig antall reservedeler holdes på lager. Ved bestilling av deler må man alltid oppgi verktøyetets modellnr., serienr. og reservedelens nr.
- (S)** * Utmärker normala reservdelar. Vi rekommenderar att tillräckligt antal lagras för serviceändamål. Uppge alltid verktygets modellnummer, serienummer samt reservedelens nummer vid beställning av reservdelar.
- (FIN)** * Viittaa tavallisiin varaosiin. Suosittelemme, että riittäviä määriä pidetään varastossa huoltotarpeita varten. Työkalun mallinnumero, sarjanumero ja varaosan numero on aina mainittava tilattaessa.

STATEMENT OF USE

Product is designed for installing and removing threaded fasteners in wood, metal and plastic.

REQUIREMENTS

This tool requires a 36V DC supply and is to be operated through a controller on a 42V DC supply.

Units available are listed below:

ESP1 Power module requires mains voltage supply, provides a single 42V DC output.

ESP2 Power module requires mains voltage supply, provides five 42V DC outputs.

ESP3 Controller unit provides three running options.



ESP4 Controller unit provides several running options and a 9 position speed selector switch.

ESP5 Combined power and controller module requires mains voltage supply, provides one running option.

Where controllers have Manual or Automatic mode options, this tool may be used in either mode.

ACCESSORIES

A wide range of accessories are available and suitable items should be selected from the relevant Desoutter catalogue.

	 WARNING
BEFORE USING, INSTALLING, REPAIRING OR CHANGING ACCESSORIES, READ AND UNDERSTAND THESE INSTRUCTIONS.	
<ol style="list-style-type: none"> 1. Tool operates through a 36V DC supply - do not connect directly to the mains. 2. Disconnect the power supply before handling the screwdriver bit or socket or dismantling the tool. 3. Keep loose articles of clothing or long hair away from the tool when in use. 4. Hold the tool correctly; be ready to counteract normal or sudden movements - have both hands available. 5. Do not use in confined spaces; beware of crushing hands between the tool and workpiece, especially when unscrewing. 6. Immediately after adjusting the clutch, check for correct operation. 7. Do not use in worn condition; the clutch may not operate, resulting in sudden rotation of the tool handle. 8. Ensure that the workpiece is properly supported. 9. Must not be used in explosive atmospheres. 10. Power tools are not insulated from coming into contact with electric power. 	

OPERATING INSTRUCTIONS

With the correct accessory fitted, connect the tool through the controller to the power supply.

Select the appropriate programme on the controller from the normal/slow start, auto reverse and timed reverse options.

Grip the tool around the motor case and press the tool into the fixing that is to be tightened; the motor will start when the controller is in Automatic mode.

When in manual mode the motor will not start until the RUN button is pressed.

The fixing is tightened to the required torque set by adjusting the tension on the clutch spring.

The clutch resets when the tool is lifted from the tightened fastener. To engage reverse rotation press the reverse button and hold the tool against the fastener.

NOTE: In tools with standard clutches, the torque control does not operate in reverse, the torque output in reverse equals motor stall torque.

Do not allow tool to stall for more than one second.

Default push start rotation is clockwise; this may be changed by pressing both run and reverse buttons together for five seconds, then releasing both together, followed by pressing either the run button (clockwise) or the reverse button (anti-clockwise).

MAINTENANCE INSTRUCTIONS

Lubrication

157833 = Molykote Plastislip PG75

273273 = BP Q5618

208893 = Rocol M204G

Do not pack gears or bearings with grease, only lightly coat. Use only the minimum amount of grease to locate components when assembling.

Assembly and Dismantling

Follow normal engineering practices and with references to the illustration build the components into sub-assemblies. Depress the latch within contact housing (11) to remove respective wire.

The NORTH POLE (white paint) of magnet (18) MUST be assembled into the transmission shaft (22) FIRST.

To Set the Hall Effect

Remove case halves (5) and screws (1).

Place the Hall Effect Carrier assembly as fully forward as adjustment will allow and retain with screws (3) very lightly. Ensure motor GREY wire is connected to '+' motor terminal.

Connect to controller; set for automatic operation; switch on mains supply; the motor should RUN.

Move the Hall Effect Carrier assembly towards the motor, noting when the motor switches OFF.

From this point move the Hall Effect Carrier assembly FORWARD ONE INCREMENT 0.5-1.0mm.

NOTE: The Hall Effect Carrier adjustment is in increments of 0.5mm.

Switch off power supply, tighten screws (3) and replace case halves.

DATA

Rated Current	= 0.4 amps.
Sound Pressure Level (dBA)	= 54 ± 2 re. CAGI-PNEUROP Test code
Vibration Level (m/sec ²)	= < 2.5 re. ISO 8662
Weight	= 0.28kg.




TORQUE RANGE

Clutch Spring

COLOUR	PART No.	TOOL SPEED	TORQUE RANGE Ncm
Blue	280413	1000	35 - 55 (3.0-4.8lbf.in)
Blue	280413	800	35 - 75 (3.0-6.5lbf.in)
Blue	280413	500	35 - 80 (3.0-7.0lbf.in)
Green	280423	800 & 500	15 - 50 (1.3-4.3lbf.in)
Red	280433	1000,800,500	5 - 20 (0.5-1.7lbf.in)
Green	280423	1000	15 - 40 (1.3-3.5lbf.in)

ACCESSORIES ONLY

Yellow	301723	1000,800,500	3.5 - 8 (0.31-0.7lbf.in)
Natural	280443	1000,800,500	2.5 - 7 (0.17-0.5lbf.in)

Part No. 280513 280533 280543 292693	 WARNING = PA 6/6, 30%gf, <0.1%Cd	 
--	---	---

© Copyright 1997, Desoutter, HP2 7DR, UK

All rights reserved. Any unauthorized use or copying of the contents or part thereof is prohibited. This applies in particular to trademarks, model denominations, part numbers and drawings. Use only authorized parts. Any damage or malfunction caused by the use of unauthorized parts is not covered by Warranty or Product Liability.



Desoutter Limited, HP2 7DR, UK